



REVISED PATENT APPLICATION

CONTROL NUMBER: 10/553,855

5

(CURRENTLY AMENDED) a SYSTEM FOR THE TRACKING AND  
MOTION CONTROL OF A PROFESSIONAL VIDEO CAMERA PERMITTING  
THE COMBINING OF BOTH REAL AND VIRTUAL IMAGES (COMPOSITING)

10

**Inventor:** Laurent Alhadeff

**Filing Organization:** Yodea Editions

15

**DESCRIPTION (CURRENTLY AMENDED)**

5 A system for the transmission of data describing  
the position in space of a video camera in motion is  
presented. It is capable of transmitting the spatial  
coordinates of the camera, in real time. By so doing, it  
permits the determination of spatial coordinates for the  
focal plane of video images. Such a device is generally  
10 known as a "motion control" or "tracking camera". A system  
for the implementation of this process is also described.

Within the context of this invention, the term  
"coordinates" should be understood in a very general sense.  
In this general sense of the term, the coordinates of the  
15 focal plane of an image are determined by: the inclination  
of the focal plane in space, the angle of the azimuth  
(yaw), the degree of elevation (pitch), and the extent of  
roll, as well as the position of the center of the image.  
This center point is defined by three spatial coordinates,  
20 arbitrarily termed  $x$ ,  $y$  and  $z$ , on an orthonormal trihedron  
with axes  $X$ ,  $Y$  and  $Z$ .

This system finds its most important , albeit not  
exclusive, applications in two principal fields:

- The characterization of images within a video  
25 stream with respect to the position in space of their focal  
planes.

- The determination, in real time, of the field  
of view of a video camera moving within a virtual decor.

### First field of application

In the film special effects industry, it is often necessary to imbed images from other sources (other films, models, virtual images...) within images filmed with a camera in motion. By knowing, with precision, the coordinates in space of each focal plane and the focal length used, it becomes a simple matter to prepare other images, whose coordinates are also known, for imbedding. The coordinates of an image's focal plane are, as described above, the inclination of the focal plane in space (given by the angles of azimuth, elevation and roll), as well as the position of the center of the image (coordinates  $x, y, z$ ). This is particularly applicable to the imbedding of virtual images in a film.

### Second field of Application

More and more, the decor of a film is composed, entirely or in part, of virtual images. Thus, it now becomes difficult, under certain conditions, to determine the framing of a video camera precisely, especially when it is in motion. In that case, it becomes necessary to visualize, in real time, an outline of the framing of the camera within a three-dimensional virtual decor. The three-dimensional decor is modeled first. When the spatial positions of the camera and the focal distance are known, the virtual image of the frame is reconstructed, in real time, by a computer program which renders it three dimensional.

A previously issued patent by the same inventor, patent No. n°=7187401, entitled "system and a method of three-dimensional modeling and restitution of an object" also makes reference to a system for the  
5 transmission of data describing the position in space of a video camera in motion by using an inertial control unit.

Coupling a camera to a inertial control unit is not new. Military drones use such systems to navigate  
10 independently . Robots within nuclear plants are equipped with cameras connected to inertial controls units. Reconnaissance aircraft take photographs guided by inertial control unit in order to construct maps in relief by the technique of photogrammetry. In this case , they use  
15 extremely heavy inertial control units (100 kg), for witch it is not necessary to correct the measurements by image analysis.

However, the presently described device is  
20 different in several ways.

- The primary function of the previously patented process is to provide a three dimensional model of an object, whereas the main function of the system described  
25 in the present application is to enable permit the facile imbedding of virtual images onto real images, for use within a film, while using a light and highly mobile (shoulder-held) camera.

- The system previously patented is integrated into  
30 camera specially designed for that purpose, whereas the

present system is attached to a previously existing camera, usually a professional video camera.

- The methods of data analysis are quite different. The previously patented device processes the data using a free-standing computer containing photogrammetric software in order to obtain a three dimensional model of the scene. On the other hand, in the present device, data analysis is performed utilizing software often referred to as "compositing programs" which enables the imbedding of images from other sources (other films, models, virtual images, etc.) onto images filmed with a camera in motion.

At present, a certain number of systems exist which attempt to respond to needs of this type. These may be divided into two principal categories.

First, there are processes associated with systems involving video cameras mounted upon robots or upon articulated arms. With these types of systems, it is certainly possible to achieve good precision. On the other hand, relatively numerous drawbacks are usually encountered, which one may summarize as follows: the apparatus is heavy and difficult to transport; it has a limited operating range; its cost is high and the system is best reserved for specialists, since its operation is complicated.

There are also systems for image processing which rely upon tracking a series of "remarkable points". These processes make use of specialized software. Once the film has been digitized, certain "remarkable points" are selected in a particular image of the film. These same points are then identified in each subsequent image by using a software method known as "point tracking" (ie, "the following of specific points"). An image processing

algorithm then enables the software to determine the position of the focal plane of each image. The main advantage of this method is that establishing the field of view is quick and easy. By way of software examples, one  
5 may cite "3D Equalizer" marketed by the Techimage company and "MatchMover" (registered trade mark) made by Realvitz.

Nonetheless, the drawbacks of this process are numerous: Image processing is long and costly; the processing of sequences lasting less than a minute may take  
10 weeks. Frequent manual interventions are required. The accuracy is mediocre. The images must be sharply contrasted; for example, the process is practically impossible in the case of images with fog, rain or dim lighting. The images must be sharp; a hazy effect perturbs  
15 the quality of the measurements, as, for example, when the diaphragm of the objective is open widely, which diminishes the depth of field. In the presence of errors engendered by the optics, these aberrations perturb the quality of the measurements (chromatic aberration, coma, astigmatism,  
20 field curvature, distortion, etc.). Systems for image compression also impair the quality of the measurements. Because the method for calculating the position of images is different, it is impossible to apply this technique to the visualization of decor in real time. Finally, it is  
25 necessary to use optical targets when the image offers little contrast, as, for example, in a film with a blue background.

The invention seeks to mitigate the drawbacks of  
30 existing systems, some of which have been outlined above, by proposing a process for transmitting, in real time, the spatial coordinates of a moving video camera. Methods for the implementation of this process are also provided.

The system, as a whole, takes the form of a light-weight apparatus to which a professional video camera is attached. It consists of a light, mobile and autonomous system, which permits, if the focal distance is known, the control of a video camera, in such a way as to facilitate the imbedding of other images into the images being filmed. It may be used as a pointer to allow the visualization, along the axis of the camera, of a virtual three-dimensional decor. There are, essentially, two principal sub-systems:

The first subsystem is intended to be integrated with a video camera. It consists of a rigid shell, in which an inertial sensing unit and its electronics are housed.

The second subsystem, which can easily be carried in a pack by the operator, is designed to process the data from the first system and to supply power to the entire system. It includes a battery, or other power source, to provide electric power to the entire system, and a light-weight electronic console, connected to the output of the inertial sensing unit, which records the data concerning the position in space of the video camera at a predetermined frequency, typically 100 Hz. The data recorded by the electronic console are indexed with respect to time.

These data may be transmitted directly by cable or by wireless technology to a supplementary computerized data processing unit, containing software for navigation within a 3D model, so that the data can be processed in real time or quasi-real time. The preferable method for accomplishing this is to place the data processing unit in a back pack, or other similar device, which is carried by the operator.



To improve the quality and precision of the measurements, supplementary components may be added to one or the other of the two subsystems.

5 As a result of the processes and systems of the invention, the precision of the measurements is independent of the quality of the images. In addition, transmission of the positional coordinates is carried out in real time.

10 In summary, the invention has as its principal objective a process for the transmission of positional coordinates of a viewing device for a sequence of video images, moving in space along a trajectory defined with respect to a predetermined reference standard, characterized by means of at least the following steps:

15 - A preliminary step consisting of attaching the above mentioned viewing device to the initial subsystem, which includes an inertial sensing unit delivering signals representing the special coordinates and the instantaneous inclination of the said viewing device with respect to the above mentioned reference standard.

20 - An initial step of data acquisition, in real time, of the said data signals during the displacement of the said viewing device along the above mentioned trajectory and of their transmission to a second subsystem which has the ability to process the data employing a  
25 prerecorded software program.

- A second step of data processing, either in real time and/or differed for subsequent analysis, in a manner so as to determine the positional coordinates.

30 Another objective of the invention is the application of this process to the characterization of the images of a video stream with respect to the position of its focal plane in space.



Another objective of the invention is the application of this process to the visualization, in real time, of the framing outline of a video camera within a virtual decor.

5           Finally, another object of the invention is to provide a system for transmitting, in real time, the positional coordinates, within space, of a moving video camera.

10           The invention will now be described in a more detailed fashion by referring to the attached drawings:

          figure 1A illustrates schematically an example of the system for transmitting and processing the data defining the position within space of a viewing device for a sequence of video images, - figure Figure 1A illustrates  
15           schematically an example of the system for transmitting and processing the data defining the position within space of a viewing device for a sequence of video images, according to one method of using the invention.

          figures 1B through 1D illustrate schematically an  
20           example of the system for transmitting and processing the data defining the position within space of a viewing device for a sequence of video - Figures 1B through 1D illustrate schematically an example of the system for transmitting and processing the data defining the position within space of a  
25           viewing device for a sequence of video images, according to a second method of using the invention.

          Figure 2 illustrates schematically an operating modality which permits the acquisition of the coordinates, in three dimensions, of the focal plane of an image, with  
30           respect to an orthonormal trihedron of reference related to a scene;

Figure 3 consists of a block diagram describing the principal steps of the process according to each of the two methods of using the invention.

5 First, we will describe examples of the system for transmitting, in real time, the coordinates of the position within space of a video camera in motion according to each of the two methods of using the invention, referring to Figures 1A through 3. In these figures, identical elements  
10 bear the same reference numbers and will not be described again, except as needed.

In Figure 1A, we have represented an initial system (system 1), which one might describe as "minimalist". This system 1 includes one video camera. In effect, the  
15 process, using the invention, as will be shown, permits disassociating the image quality from the precision of the measurements furnished by the system. In other terms, a high precision of measurement may be obtained even when the images are of poor quality. Therefore, the system is not  
20 sensitive to conditions such as weak lighting, haziness, etc.

As noted above, the system for transmitting, the spatial coordinates of a video camera (10) in motion, in real time, consists of two principal subsystems:

25 The first subsystem (11) includes an inertial sensing unit and its electronics (not specifically shown in the drawing). It consists of a rigid shell (110), in which the inertial sensing unit and its electronics are housed. This shell is intended to be attached to the video camera  
30 (10) by any appropriate method of fixation, permanent or adjustable (ties, screws, etc.), symbolized by reference 111.

The second subsystem is a storage component (12) which can be conveniently carried in a pack by the operator (not shown in Figure 1A). This storage unit (12) is designed to process the information provided by the first subsystem (11). In addition, it supplies power to system 1 in its entirety. It includes a battery, or other device (not shown) for providing electric power, and a light-weight electronics console, connected to the output of the inertial sensing unit, which records the data concerning the position in space of the video camera (10), via the frame (11) which is attached to it, at a frequency typically in the range of 100 hertz (Hz).

The data are transmitted to the second subsystem (12) via a connection (112), wired or wireless (electromagnetic waves, etc.). It should be noted that this connection (112) may be bi-directional, in which case a wired type of connection is used, in series or in parallel.

Figure 1B illustrates an example of a system transmitting, in real time, the special coordinates of a moving video camera, employing a second method of utilizing the invention, which one might describe as "complete". This system will hereafter be referred to as system 1'.

The video camera and first subsystem may be identical to those depicted in Figure 1A. Nevertheless, the video camera and the first subsystem will hereafter be indicated by 10' and 11', since one or the other may be "completed" by the addition of certain modules which will be described later. The first subsystem (11'), as previously, is coupled to a video camera by any appropriate method (indicated in the drawing by 111').

A fundamental difference between the first and second methods of operation relates to the fact that the data generated by the first subsystem (11') are transmitted

directly to a data processing unit (reference 20) containing a stored software program. The latter may be easily placed in a back-pack (200), or other similar device, carried by the operator (OP).

5           Figure 1C illustrates schematically one possible configuration of the system for data processing (20), in the form, for example, of a micro-computer (4), placed in a back-pack (200) and communicating with the first subsystem (11') via connections (112') similar in type, if not  
10 identical, to those shown in Figure 1A.

The micro-computer (4) consists of a group of modules and circuits mounted on a chassis (40). The principal modules and circuits of the micro-computer (4) are the following:

15           A battery for providing electric power, for example a lithium battery of 12 volts and 10 ampere hours, with an associated power chopping unit, so as to avoid using heavy transformers (401); the power supply furnishes a range of output voltages and currents, of appropriate  
20 amplitudes, to the other components; it is indicated by the general reference VS;

A digital data processing unit using stored software programs, shown as 402, including the various classical computer components (not shown) such as  
25 microprocessor, random access memory (RAM), etc. and, most notably, a video card, preferably of the 3D type;

A large hard drive memory unit (403), consisting, for example, of two magnetic discs, each having a capacity of 80 gigaoctets (Go);

30           A display unit (404), receiving signals from the 3D video card, mentioned above;

Data entry devices such as a keyboard (405) and a pointing device (406), mouse, ball, etc., for inputting comments, additional data, as well as instructions for synchronization and/or for data processing;

5           Electronic circuits (407) for processing the signals generated by the first subsystem (11', figure 1B), interfacing with the digital data processing unit (402) by means of a suitable electronic circuit card (for example, a serial port); and

10           Input and output ports for handling various protocols, as well as electronic circuits for interfacing with external devices, such as "IEEE 1394" or "Firewire", "USB", "VGA", video, sound, "Bluetooth", "Ethernet", "wireless", "802.11", etc., which are grouped together  
15 under the single reference 408.

          Connectors (409) are also envisaged for linking the micro-computer, by cable (112', figure 1B), to the primary subsystem (11'). *A priori*, the cable will carry signals of several types: electronic signals carried over wires  
20 (1120'), (a serial bus, for example, or the like), electric power supply signals (1121') and optical signals carried over optical fibers, for example from the optical fiber gyrometers housed in the first subsystem (11'). A corresponding connector (not shown) is envisaged within  
25 that subsystem (11'). Naturally, other types of linkages could be provided, as well, such as radio links (for example, using the "Bluetooth" technology, mentioned above) and direct optical links (signals modulating an infrared carrier, for example) between the first subsystem (11') and  
30 various elements of the micro-computer (4).

In place of the data entry units 405 and 406, or in addition to them, one could use a PDA (Personal Digital Assistant). This PDA would be linked to the micro-computer

(4) by a cable (210) going to, for example, the connector indicated by reference 409.

5 Preferably, the circuits (421) would feed, through the linkages (1121') to the connector 409, all of system 1', that is to say, the first subsystem (11'), and the video camera (10'), as well.

10 In order to improve the measurements obtained and/or to provide greater facility of data processing, one could expand and/or modify one or both of the first and second subsystems (11' and 2, respectively).

15 In order to improve the accuracy of determining the localization coordinates of the video camera (10'), one might add one or more of the following modules, located in the video camera (10'), the first subsystem (11') and/or the second subsystem (2):

A gyrometer consisting of three orthogonal bobbins of monomodal optic fibers (for example, using bobbins 80 mm in diameter, each one containing 1000 meters of optic fiber);

20 - A tri-flux rotary magnetometer;

- Two inclinometers, orthogonal with respect to the principal plane of the apparatus, that is to say, of the video camera (10');

25 - A satellite localization system (22) of the GPS (Global Positioning System) type or, in the near future, of the type called "GALILEO", which would provide more precise localization data, would measure the variations in localization and would correct for inertial components. This unit (22) would communicate with the appropriate processing circuits (not shown on Figure 1C), housed in the  
30 chassis (40) of the micro-computer (4);



-An electronic localization unit (using electromagnetic or electrostatic fields) to measure variations in localization and to correct for inertial components;

5           - An additional magnetometer, of a single or several fluxes, static or dynamic (for example rotary, in order to eliminate parasite components), in order to measure variations in localization, essentially with respect to the earth's magnetic field, and to correct for  
10           inertial components;

- An odometer to measure variations of localization and to correct for inertial components;

- An electronic system giving the operator and the entire system an estimate of the drift of the localization  
15           units, in real time;

- A trihedron of three ultrasound emitters to generate information on the localization of the video camera (10');;

- A temperature sensor to improve the accuracy of  
20           data from the inertial sensing unit.

To provide optimum data synchronization between the sequences of images captured by the video camera (10'), one could install a high precision quartz timer, as well. One  
25           could also install a small, auxiliary on-board camera, coupled to the main video camera (10'). The stream of images from this auxiliary camera, even though of poor quality, if integrated with the various methods for localization of the main video camera (10'), would  
30           facilitate the synchronization of the stream of images, of superior quality, obtained by the primary video camera



(10') with its localization measurements. One might also add a microphone (23) to the second subsystem (2) to capture the comments of the operator (OP) and/or the synchronization beeps, in order to facilitate the editing of the video images and make the editing more secure. Finally, one could utilize an initialization terminal (3), which establishes the initial starting point of the camera, and is schematically illustrated in Figure 1D. The video camera (10') is placed in a housing (30), which defines the camera's original starting point for the movement and localization sensors located in the first subsystem (11')

It is certainly possible to make use of a more elaborate video camera than the one described heretofore, particularly with respect to devices called "man-machine interfaces". In particular, the video camera (10') might be provided with:

- Push-buttons;
- Two rotary knobs, used to regulate the speed of image acquisition and the identification of "remarkable points"; and/or
- A viewing screen, preferably of the Liquid Crystal Display (LCD) type, with a resolution of 400x300 pixels, for example.
- One might also provide the operator (OP) with "virtual goggles", which could replace the screen of the video camera (10').

In both configurations that have just been described, (Figure 1A, for the first, and Figures 1B through 1D, for the second), the first subsystem (11 and 11', respectively) is made up of at least the basic devices

for instantaneously monitoring position and speed by inertial methods (i.e., gyrometers and accelerometers).

The first subsystem (11 or 11') is attached to a video camera (10 or 10'). This system, as conceived by the invention, allows one to effect what has previously been called "motion control". The invention will find application, as will be shown, in two large areas of activity: the characterization of images, within a video stream, with respect to the position of their focal plane in space and the visualization, in real time, of the framing outline of a video camera (10 or 10') within a virtual decor.

These operations assume that one is able to determine, at each point in time, a certain number of parameters related to the image perceived within the viewfinder, notably the spatial coordinates of the video camera (10 or 10') with respect to a reference point and the focal length utilized.

Figure 2 illustrates schematically the method of operation which permits acquisition of the coordinates, in three dimensions,  $x_n$ ,  $y_n$ , and  $z_n$ , of the focal plane (FP) of an image (I), with respect to an orthonormal trihedron of reference, XYZ, related to a scene (SC).

One must refer, again, to the second method of operation, depicted on Figures 1B through 1D, understanding that all that will be discussed applies equally to the first method of operation (figure 1A). One assumes that the axis ( $\Delta_i$ ) of the video camera (10') intersects the focal plane (FP) of the image (I) at its center ©. The video camera (10') follows a given trajectory ( $t$ ), causing it to pass, for example, from one point ( $p_1$ ) with initial coordinates  $x_1$ ,  $y_1$  and  $z_1$  to another point ( $p_n$ ) with final coordinates,  $x_n$ ,  $y_n$  and  $z_n$ , while passing through an intermediate point ( $p_i$ ) with instantaneous coordinates  $x_i$ ,

$y_i$  and  $z_i$ . The velocity and the instantaneous acceleration of the video camera (10') may be of any magnitude and may vary along the trajectory ( $t$ ). At each point, one may define, besides the instantaneous coordinates  $x_i$ ,  $y_i$  et  $z_i$ , with respect to the reference trihedron XYZ, three series of values for instantaneous inclination, characterized by the three angles, called angles of elevation, ( $\alpha_i$ ), azimuth ( $\beta_i$ ) and roll ( $\gamma_i$ ) of the axis ( $\Delta_i$ ), with respect to the same reference trihedron XYZ.

Once the first subsystem (11') has been attached to the video camera (10'), it follows the latter's movements at the same velocity and also follows its inclination, as defined by the angles of elevation, ( $\alpha_i$ ), azimuth, ( $\beta_i$ ) and roll ( $\gamma_i$ ). The measuring devices based on sensors of position and instantaneous velocity of an inertial nature, housed in the second subsystem (11'), can then generate data concerning its position (spatial coordinates), instantaneous velocity and inclination throughout the camera's course of motion. The transmission of these data is carried out using the linkage #112, typically at a frequency of 100 Hz. These data are recorded by the data processing unit (4) for later analysis and/or processed in real time or quasi-real time, preferably followed by a recording of the results of analysis, to be reserved for later use.

Other parameters may also be followed, such as the focal point used for each of the various views.

As has already been mentioned, initial standardization of the measuring devices housed in the first subsystem may be accomplished by placing the video camera (10') in the housing (30) of the initialization terminal, at a predetermined area of the scene (SC), for example at coordinates  $x_1$ ,  $y_1$  and  $z_1$ . In this case, one can obtain absolute measurements. If not, in other words,

without the initialization step, the data generated will represent relative measurements.

5 We will now describe the principal steps for the first method of using the invention, by referring to block diagram 5 on Figure 3. We will also refer, as necessary, to the second method of utilization and to references appearing on Figures 1B through 2.

Step 1 (block 51): This is a preliminary step involving the configuration of the system.

10 First of all, one attaches the video camera (10') to the first subsystem (11'). The first subsystem (11') is solidly attached to the video camera by means of a special screw or by any other suitable mechanism (111'). Preferentially, this fixation of the camera to the first  
15 subsystem (11') is accomplished via the screw threading intended to receive the base of the camera (10').

A configuration description is included in the second subsystem (2) in the form of a text file on system configuration. Information relative to the hardware and  
20 software used is also provided in this file. Certain parameters may be reconfigured at this step.

Later on, as data is being progressively acquired, the models for predicting the behavior of the inertial sensors may be refined by applying procedures for  
25 algorithmic processing of the data.

Step 2 (block 52): Initialization of the system.

Before beginning to film, it is desirable to initialize the inertial sensing unit, located within the first subsystem (11'). The position of the video camera  
30 (10') at the time of this initialization procedure then becomes the point of origin, based on which all subsequent

movements are calculated. The position measurements are, then, measured relative to that starting point.

As needed, if determining the position of the video camera using absolute coordinates becomes necessary (for example, for greater ease in imbedding a synthesized image or for the superimposition of successive fields), it is sufficient to know the coordinates of the point of initialization. To know the position of this point in reference to terrestrial coordinates, it is relatively quick and easy to use a GPS module (22), or any other appropriate technique, notably those known as "geometric".

### Step 3 (block 53): processing of inertial data

This step allows one to analyze the localization data, in real time, and to determine the motion of the video camera (10') (including its inclination).

The position of the video camera (10') is determined by a localization system of the inertial navigation type, essentially based on the use of gyrometers and accelerometers contained within the first subsystem (11').

These principles are well known and are described in the following articles:

- « Inertial navigation system analysis », by K.R. Britting, published by Wiley-Interscience, New York, '1971); and

- « Inertial navigation systems », by C. Broxmeyer, published by McGraw Hill, New York, (1964).

After a predetermined lapse of time, it is usually necessary to recalibrate the system using the initialization terminal (3), which serves as the point of reference. The measurement differences with respect to this reference point are determined. These differences are then uniformly distributed over the prior localization measurements, so as to compensate for measurement errors.

One may also use other sensors of position and distance, such as those which have been previously mentioned: GPS, magnetometers, inclinometers and entry odometers. These sensors permit redundant determinations and, thereby, improve the accuracy of the measurements. The estimated drift of the position measuring sensors of the apparatus may also be transmitted to the operator (OP). These measurements are also corrected by image processing. This type of processing is well known and has been well described in the following articles:

- El-Sheimy N. Shwarz, K.P, "Integrating Differential GPS with an inertial navigation system (INS) and CCD Cameras for a Mobile GIS Data Collection System." Proceedings of the Canadian Conference on GIS", Ottawa, Canada, June 6-10, 1994, pp.241-248 ;

- Abdulah Q., "Evaluation of GPS-Inertial Navigation System for Airborne Photogrammetry", ASPRS/MAPPS Softcopy Conference", Arlington, Virginia, July 27-30, 1997 ; and

- Skaloud J., Cramer M., Schwarz K. P., "Exterior Orientation By Direct Measurement of Camera Position and Attitude", XVIIth ISPRS Congress", Vienna, Austria, July 9-19, 1996, International Archives of Photogrammetry and Remote Sensing, vol 31, part b3, pp125-130, 1996;

The inclination of the video camera ( $10'$ ), i.e., angles of elevation,  $\alpha_i$ , azimuth,  $\beta_i$ , and roll,  $\gamma_i$ ), and



consequently the inclination in space of the focal plane (FP) of the image (I), is defined primarily by a trihedron of three gyrometers placed along three distinct, non-coplanar axes and located in the first subsystem (11').

5           The electronics associated with the three gyrometric sensors deliver data on the incremental rotations  $\Delta\alpha, \Delta\beta$  and  $\Delta\gamma$  about the three axes. On the basis of these increments, the angular positions  $\theta_x, \theta_y$ , and  $\theta_z$  are calculated by changing the frame of reference using  
10           arithmetical computations known as « quaternions ».

The instantaneous position (coordinates  $x_i, y_i$  and  $z_i$ ,) of the images captured by the video camera (10') and consequently the position of the center © of the image (I) is primarily provided by the three accelerometers.

15           The distances traveled along each of the three axes ( $x_i, y_i$  and  $z_i$ ,) are calculated by successive integrations making use of calculations of dynamics based on the acceleration data supplied by the trihedron of three accelerometers.

20           The accelerometers and the gyrometers cooperate to calculate the data localizing the video camera (10'), typically at a frequency of 100 Hz, as mentioned above.

          The movements of the video camera (10') are calculated continuously by means of established numeric  
25           integration algorithms (for example, of the "predictor-corrector" type, such as "Range, Kutta" and "Adam"), in order to interpolate intermediate points.

          Factors related to the earth, influencing the position measurements, must also be integrated into the  
30           calculations. In fact, it is generally necessary to take two factors into account when calculating motion within a Euclidean frame of reference. The two factors are, first,



the roundness of the earth and, second, its velocity of rotation.

5 In order to compensate for errors due to the roundness of the earth, one usually uses a gyrometric correction, so as to take account of the earth's curvature during translational movements.

10 In order to adjust for drift due to the acceleration of the earth, it is necessary to integrate latitude and velocity data, so that the apparatus automatically decrements the values that are added by "Cariolis" acceleration. To do this, latitude and velocity are automatically measured using a GPS unit.

15 It is also useful, if not necessary, to correct for errors derived from drift related to the inertial character of the measuring equipment.

20 It is known that the values coming from the gyrometers drift over time as a function of temperature and of magnetic field. Therefore, it is necessary to regularly recalibrate the gyrometers, both statically and dynamically.

25 It is also known that the values provided by the accelerometers drift, with an oscillation of about 84 minutes. This drift is known as "Shuler's law". The accelerometers also drift because of Cariolis acceleration (the "Foucault" effect), which depends on the latitude and the velocity of the moving body.

In order to correct for these errors and for drift of an inertial nature, one should implement, simultaneously, three series of compensation measures:

30 - The first set of measures compensates for the drifts of the gyrometers;

- The second set of measures compensates for the drifts of the accelerometers; and

- The third set of measures compensates for the drifts of the inertial sensing devices.

5           These three types of corrective measures are described below:

10           Gyrometers of very high precision, cooperating with gravity sensors, are capable of determining the axis of rotation of the earth, and thus of determining the direction of geographic north and the direction to the earth's center of gravity. In this way, it is possible to reset inertial type sensors automatically.

15           In order to compensate for "Schuler" drift, measurements are taken from the accelerometers over a period longer than 84 minutes. This initialization time enables one to determine the characteristics of the "Schuler" period for each accelerometer. On the basis of these characteristics and by using an electronic clock, the value of the period is continuously decremented from the results given by the accelerometers.

20           To compensate for errors due to the "Schuler" and "Coriolis" laws, predictive modeling is used, based upon the use of so-called "Kalman" filters.

25           To compensate for drift of the inertial sensing unit, a resetting of the unit is performed after a predetermined lapse of time. For this purpose, the initialization terminal (3, in Figure 1D), serves as the point of reference. The difference between the measured positions and the position of the reference point is determined. This difference is then distributed among all the previous measurements, in order to compensate for measurement errors.

Measurements are taken with the gyrometers and the accelerometers, under various conditions. These measurements are then input into a software program, whose specific function is to model the behavior of gyrometers and is part of the second subsystem (2). The model permits the correction of errors, in real time.

Data acquisition from auxiliary sensors (measurements of the earth's magnetic flux, GPS measurements, measurements supplied by the inclinometers) permits the correlation, in real time or later, of data relating to trajectory ( $t$  in Figure 2).

In a preferred method of utilization, the system (1') is capable of interfacing with auxiliary positioning systems, such as:

- Information coming from odometers is utilized, if the video camera (10') is used on a vehicle equipped with an odometer.

- Information derived from a rotary laser may be utilized. Three optical reference targets, similar to the initialization reference point (3 in figure 1D), are installed around the area to be modeled. The laser identifies them several times per second. It can thus determine its position. This measurement is accurate over areas of several tens of meters. This permits the correction of measurements from the inertial sensing unit.

A locating system based upon a trihedron generating an electromagnetic or an electrostatic field may be added.

It may also be necessary to correctly manage redundancies of errors and/or redundancies of information.

All the methods seeking to provide additional information can be combined. In fact, information

redundancies are most advantageous for increasing the amount and accuracy of available information and thus permitting the establishment of correlations.

5 In order to best utilize such redundancies, it is helpful to use conventional "gradient decent" or "quadratic programming" types of algorithms (such as the type proposed by Karmaker, or the More and Toraldo type, or the Markhov model type, etc.) so as to obtain near-certain values for each parameter, despite errors of measurement. These  
10 algorithms also serve to eliminate aberrant values and to reconstitute missing values.

These methods are well known and are particularly well explained in:

15 "Numerical Recipes in C++", in: The Art of Scientific Computing, William H Press, Saul A. Teukolsky, Brian P. Flannert and William T. Vetterling, eds., January, 2002.

Finally, another problem to be resolved relates to the shaking of the video camera (10').

20 This increases the difficulty of making accurate localization measurements, when the video camera (10') is hand held by the operator (OP in Figure 1B). In effect, this method of operation introduces "noise" in the measurements. Studies have shown that this noise due to camera shaking generally occurs at a frequency in the  
25 region of 10 Hz.

Therefore, it is useful to incorporate a "deadening unit" to adjust for sudden and/or frequent variations in trajectory ( $t$  in figure 2) measurements, as well as shocks.

30 It is known that accelerometers are most accurate within a certain range of acceleration and frequency. Therefore, it is desirable to amortize the variations in

trajectory (t) that fall outside this range of predilection. This method of operation allows one to optimize the measurements coming from the accelerometers. Another advantage is that it smoothes the curve of the trajectory followed by the video camera (10') and thus diminishes the effect of noise contaminating the measurements.

A means of obtaining this effect is to stabilize the video camera (10') and the case of the first subsystem (11'), containing the gyrometers and accelerometers using shock-absorbers (not shown in Figure 1B).

Step 4 (block 54): data acquisition.

This step consists of acquiring all necessary information and then insuring that all the data is "time-stamped".

These data concern primarily:

- Capturing a stream of data from the inertial sensing unit; and
- Storing, within a temporary folder, data concerning the increments in rotation  $\Delta\theta_x$ ,  $\Delta\theta_y$  and  $\Delta\theta_z$ , along the axes of each of the three gyrometers, as well as the increments in translation  $\Delta\theta_x$ ,  $\Delta\theta_y$  and  $\Delta\theta_z$ , along the axes of each of the three accelerometers at a frequency of 100 Hz, as indicated previously; and
- Data on the focal length used.

Optionally, one may record other sorts of data, such as:

- Data, at a frequency of 10 Hz, coming from the two inclinometers;

- Data concerning absolute position, coming, at a frequency of 5 Hz, from a GPS unit;
- Laser telemetry data, at a frequency of 1000 Hz;
- 5       - Data, at a frequency of 1 Hz, from internal temperature sensors;
- Asynchronous recordings of sound sequences;
- "Time-stamped" data generated by the tri-flux magnetometers, synchronized with the images taken by the video camera (10');  
10
- Data generated by ultrasonic position measuring devices;
- Data concerning various optical parameters: focal length, picture-taking speed (exposure time for each image) and focusing distance of the video camera (10'), these data being synchronized with each image taken; and  
15

Recordings of commands given by the operator.

Step 5 (block 55): improving image localization measurements by image analysis:

- 20       Localization of the position of the video camera (10') by image analysis essentially serves to corroborate and fine-tune the measurements derived from the gyrometers and accelerometers.

25       One processes the redundant data using "descending gradient" or "quadratic" algorithms, cited above, which provide near-certain values for the desired parameters, in spite of measurement errors. These algorithms permit the



elimination of aberrant values and the reconstitution of missing values, as discussed previously.

5 In the preferred utilization mode, one also uses "remarkable points" and implements the "point tracking" technique.

10 In effect, the localization of camera positions may be refined by the selection of "reference points" on each image. These points of reference are called the "remarkable points" of a subject for computer modeling, which one then identifies on a maximum number of images. The analysis of these "remarkable points" permits the calculation of camera positions.

15 The technique called "point tracking" is used to locate these "remarkable points" in a series of images, since the images have been filmed as part of a single video or video sequence, in which the images follow one another. Point tracking is a well known software method for image analysis, which permits the automatic following of one or more image points, of the same type, of a subject throughout a video sequence, in which the images follow one another. It is known that this technique is presently a subject for study and for industrial implementation. Nonetheless, its reliability has often been called into question, because of certain problems, especially when the remarkable points are not sufficiently different from adjacent points. This technique is rendered much more reliable and easier to use, when the methods of the invention are implemented, because, in that case, one already knows the characteristics of the image (e.g., the coordinates of the image focal plane) with some precision, from the physical parameters already defined. As a result, the software need "search" only within a well defined region of the image.

20

25

30



A substantial number of software are known which will perform this type of analysis and this "tracking" method is a help in localizing images. It permits the automatic analysis of a large number of reference points. It is evident that the greater the number of reference points the greater the degree of refinement in image localization measurements that is obtained.

As a practical matter, in order to assure optimum measurement of trajectory, one adds a laser telemetry device (not shown) to the video camera (10') and/or to the first subsystem (11') which is coupled to it, in order to measure the distance between a particular point and the object to be modeled. This point, whose distance is now known, is automatically taken as being a remarkable point. It is therefore a point that is followed by "tracking". Analyzing curves displaying the positions of these reference points over time makes it possible to accurately determine the motion of the reference points relative to the video camera (10'). If the modeling is being performed within a stationary space, it becomes very easy to determine the movements of the video camera (10'), itself. In this way, it is possible to correct the measurements provided by the gyrometers and accelerometers of the first subsystem (11').

One may also use optical targets as points of reference.

One powerful technique for obtaining points of reference on images is to install optical targets around the subject to be modeled. These targets are equipped with light emitting diodes. Their positions on the images may then be recognized automatically.

Step 6 (block 56): data synchronization.

The inertial sensing unit within the primary subsystem (11') transmits its data at a frequency of several hundred Hertz. The problem is to synchronize the data concerning the position of the video camera (10') transmitted by that unit with the filmed images, the goal being to characterize the images with respect to the position of the video camera (10') at the moment they are filmed.

It should be noted that certain video cameras can transmit, digitally and in real time, data concerning sound synchronization, the position of the focal plane (which is an extremely important, if not essential, parameter), the type of film, light measurements, etc., data which should also be synchronized with respect to the position data.

Several different solutions to the synchronization problem could be adopted using the invention, among which are the three that follow:

Solution 1: Images-position synchronization can be done by using the traditional images-sound synchronization method utilized by the movie industry. One films a hand-clap. Then one "pastes" the film frame where the clapping hands come together to the moment on the sound track where one hears the sound of the clap.

The second subsystem (2) contains a microphone (23 in figure 1B). One synchronizes the position data stream with the sound, which has been recorded simultaneously. Then one need only find the sound of the hand clap on the sound track to complete the synchronization of the images with the positional data stream.

Solution 2: The video camera (10') contains circuits which generate an output signal indicating the moment at which the operator (OP) begins to record a new sequence of images. This signal is received by the

microprocessor (4) of the second subsystem (2) and the recording of positional data is initiated immediately.

Solution 3: One can attach a small, auxiliary video camera (100'), light-weight and of low definition, to the primary video camera (10') or to the first subsystem (11'). In this case, the recording of the images and of the position data stream is simultaneous. The direction of the objective of the auxiliary video camera (100') is the same as that of the primary video camera (10'). As a result, the little video camera (100') films the same scenes with the same positions. It suffices, then, to superimpose the two image streams to synchronize the images from the primary video camera (10') with the data stream.

Step 7 (block 7): data storage

The images taken by the video camera (10') are characterized by the six coordinates of position, but also with respect to the following parameters:

- The physical configuration of the system (1');
- Time-stamping: the precise time at which the images were captured;
- Movement: acceleration, velocity and trajectory
- Focal length of the video camera (10'): type of focal length used or zoom position, if used;
- Position to which focusing distance is set;
- Picture-taking speed: exposure time for each image;
- Lens aperture during filming;

- Ambient brightness, while filming in one or more zones;

- Ambient temperature;

- Estimates of measurement errors in data from the gyrometers and accelerometers;

- Sound files

- Video files

These data are integrated into a database stored on the hard drive (403) of the data processing unit (4) of the second subsystem (2).

Step 8 (block 58): subsequent analysis of the characterized images.

The operator (OP) may, at his/her leisure, exploit the data base of characterized images in order to modify them *a posteriori*.

As has been mentioned previously, the invention has multiple and varied applications, notably the following:

Application 1: In the film special effects industry, there is often a need to imbed synthetic images into images filmed with a camera in motion. If one knows, with precision, the spatial coordinates of each image and the focal length employed, it becomes easy to fit the synthetic images into the various images of the film, which is exactly what the processes of the invention permit. The coordinates of the focal plane (FP) of an image (*I* in figure 2) are, as previously defined:

- The inclination of the focal plane in space: the angles of elevation,  $\alpha_i$ , azimuth,  $\beta_i$ , and roll  $\gamma_i$ ; and

- The position of the center of the image ©: the coordinates being  $x_i$ ,  $y_i$  et  $z_i$ .

5        Application 2: Films photographed with shoulder-held cameras may be subject to sudden variations in trajectory, as well as to shocks and/or vibrations. Knowing the image positions may serve to smooth out an image sequence, especially thanks to the use of existing image interpolation software. Again, the use of the invention permits this goal to be attained.

10        Application 3: To give slow motion effects without having jerky images, the special effects industry uses special software to create "virtual" images between two successive images that have been actually filmed. Knowing the trajectory of the focal plane, as the use of the  
15        invention allows, makes this interpolation of images rapid and reliable.

Application 4: A traditional cinema trick involves superimposing images. A classic example is to film one person, then to film the same person in a different place  
20        in the scene and, finally, to superimpose the two images. The person who has been filmed appears to be in two places at once. This effect, which is relatively easy to accomplish when the image planes are stationary, becomes much more difficult when they are in motion. It is then  
25        necessary to synchronize the two image sequences in which the image planes cover the same areas, and this is exactly what the invention permits one to do.

          Applying a second method of using the invention, the invention also permits navigation within a three-  
30        dimensional universe, in real time.

          The steps for utilizing the invention in its second mode are similar, if not identical, to those just described for the first mode, at least as far as the first four steps

are concerned. One then moves on to the step arbitrarily called "Step 9" in the block diagram of figure 3, even though this step, in reality, follows the fourth step, as will be explained later.

5           Be that as it may, the important thing here is to obtain positional data in real time. These data are provided at a frequency of 100Hz.

10           Step 9 (block 59): obtaining a "pointer" in three-dimensional space in order to navigate in a virtual universe.

15           The data relative to the position of the video camera (10'), the images taken, as well as the focal length utilized are transmitted, in real time, to the second subsystem (2), more precisely, to the data processing unit (4) via an appropriate connection (112'): wire cable, optical or wave connection.

20           The data processing unit, using stored software programs, contains software for three dimensional representations, which operates in real time. One could use one of the commercially available software programs, such as "Director" distributed by the Macromedia Company or "3DS max" distributed by a company called Discret (both names are registered trademarks).

25           This second mode of utilization of the invention finds application in the following situation (the list is not exhaustive):

30           The scenes of a film are increasingly composed of synthetic images, in all or in part. Under these conditions, it often becomes difficult to select the exact framing of the video camera (10'), especially when it is in motion. It then becomes necessary to visualize, in real time, an outline of the framing of the video camera (10')

within a virtual decor. One makes the assumption, here, that this three-dimensional decor has already been modeled. When the positional coordinates and the focal length of the video camera (10') are known, in real time, the virtual  
5 image of the framing may be reconstituted, in real time, by software for three-dimensional representation.

Having read the preceding, one can easily ascertain that the invention attains its goals.

Nonetheless, it should be clear that use of the  
10 invention is not limited to only those particular applications described explicitly, in particular with reference to figures 1A through 3.

Similarly, the choice of individual components or modules depends upon technological factors best left to the  
15 determination of the professional and have not been specified exactly, in order to better describe the overall technical characteristics of the invention.

It must be remembered that the invention's usefulness is by no means limited to those applications  
20 specifically described.